

HT-S5800 5.1.2-Channel Dolby Atmos® Home Theater Package















Movie Night Will Change Forever

What an awesome way to experience game-changing Dolby Atmos® sound! Everything you need to create a face-melting entertainment system is right here in one simple package, starting with a 115 W/Ch A/V receiver that connects all your media players and sends video to the TV via a single HDMI® cable—from your old analog game consoles to the latest 4K/60 Hz video with 4:4:4 color space and 21:9 cinema aspect. Want full Smart TV capabilities? Plug a media streaming stick into the rearside STRM Box port and enjoy a wealth of audio and video streaming apps. Once you've connected the speaker system—which allows multidimensional Atmos soundtracks to flow above and around you—AccuEQ optimizes the sound to suit the unique shape of your room. We've also included Bluetooth technology so you can hear streamed audio with Onkyo's legendary clarity and dynamism. Unleash tomorrow's entertainment at home today!

HIGHLIGHTS

- Supports Dolby Atmos® up to 5.1.2 Channels
- 115W per Channel
- HDMI® 4 In / I Out (4K UltraHD / HDCP 2.2 / 4:4:4)
- Pure Driving Power from Discrete Amp Technology
- Bluetooth Wireless Audio Streaming
- Simple Rear Panel Layout for Easy Connection

HT-R494 7.1-Channel A/V Receiver

- 115 W/Ch (6 Ohms, 1 kHz, 0.9% THD, 1 Channel Driven, FTC); 65 W/Ch (8 Ohms, 20 Hz–20 kHz, 0.7% THD, 2 Channels Driven, FTC)
- 4K/60 Hz-Capable HDMI® Terminals with 4:4:4 Color
- Space for UltraHD Entertainment (4 In/I Out)

 Bluetooth Version 2.1 + EDR Capability (Compatible Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer to Improve Compressed Digital Audio Quality (Bluetooth Audio Included)
- Phase-Matching Bass Boost for Deep Bass and Clear Mid-Range
- AccuEQ Room Acoustic Calibration
- WRAT (Wide Range Amplifier Technology)
- H.C.P.S. (High Current Power Supply) Massive High Power
- Discrete Output Stage Circuitry
- PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology for S/PDIF Audio

- Dolby® TrueHD and DTS-HD Master Audio™ Decoding
- HDMI Support for 4K/60 Hz, 3D, Audio Return Channel, DeepColor™, x.v.Color™, LipSync, Dolby Atmos®, Dolby® TrueHD, DTS-HD Master Audio™, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC
- TI Burr-Brown 192 kHz/24-bit DAC for All Channels
- · Advanced 32-bit DSP Chip
- 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Theater-Dimensional Virtual Surround Function
- CinemaFILTER™
- Direct Mode
- Double Bass Function
- Non-Scaling Configuration
- A-Form Listening Mode Memory
- STRM Box Port (Rear) for Powering Media Streaming Sticks
- 2 Component Video Inputs (Rear)
- 3 Composite Video Inputs (I Front/2 Rear)
- 3 Digital Audio Inputs (2 Optical and I Coaxial)
- 7 Analog Audio Inputs (I Front/6 Rear)
- Subwoofer Pre-Out
- Headphone Jack
- Crossover Adjustment (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control
- (Up to 500 ms in 10 ms Steps at 48 kHz)
- Overlaid On-Screen Display (OSD) via HDMI with Quick Set-Up
- HDMI Passthrough Function
- Tone Control (Bass/Treble) for Front L/R Channels
- 3-Mode Display Dimmer (Normal/Dim/Dimmer)
- 40 FM/AM Random Presets
- RIHD (Remote Interactive Over HDMI)
- Full-Function RI (Remote Interactive) Remote Control

HTP-594

5.1.2-Channel Home Theater Speaker System

SKF-594

2-Way Bass Reflex Front Speakers/Full-Range Acoustic Suspension Height Speakers

- 5" (12 cm) Cone Woofer
- I" (2.5 cm) Balanced-Dome Tweeter
- 3 1/4" (8 cm) Cone (Separately Powered By Height Channel)
- Max. Input Power: I30 W
- Wall-Mounting Capability

SKC-594

2-Way Bass Reflex Center Speaker

- 3 1/4" (8 cm) Cone Woofer x 2
- I" (2.5 cm) Balanced-Dome Tweeter Max. Input Power: I30 W
- Wall-Mounting Capability

SKR-594

Full-Range Acoustic-Suspension Surround Speakers

- 3 1/4" (8 cm) Cone
- Max. Input Power: I30 W
- · Wall-Mounting Capability

SKW-593

Bass Reflex Powered Subwoofer

- 10" (25 cm) Cone
- Rated Output Power: I20 W (Minimum Continuous Power, 4 Ohms, 100 Hz, 1%, FTC)
- Energy-Saving High Power Amplifier
- Down-Firing Design



HT-S5800 5.1.2-Channel Dolby Atmos® Home Theater Package

Extraordinary Dolby Atmos®

Dolby Atmos transports you into an extraordinary surround sound experience with captivating multidimensional sound objects that fill your room and flow all around you. This 7.1-channel receiver powers a 5.1.2-channel Dolby Atmos speaker setup: 5.1 standard surround configuration plus two height channels inside the front speakers.





Top Quality Speaker System

Onkyo knows a thing or two about building great speakers, having almost 70 years' experience in Hi-Fi. The included speaker package features precision drivers housed in solid cabinets—the front speakers also housing up-firing height drivers that unlock the magic of Dolby Atmos.

HDMI® 4 In / I Out for UltraHD

All HDMI terminals support the latest TV video displays, and HDCP 2.2 copy protection encoded in content from movie studios, broadcasters, and streaming services, for nextgeneration UltraHD.



HDCP2.2

True Power from Discrete Amplifiers

Discrete amps deliver high instantaneous current to increase speaker control for accurate and dynamic audio reproduction. This precise power is the cornerstone of Onkyo's amplification philosophy.



Bluetooth Audio Streaming

Stream virtually any audio from your smartphone, tablet, or PC to your home cinema for clear and powerful sound.



AccuEQ Room Acoustic Calibration

AccuEQ measures and corrects speaker distances, output levels, crossover frequencies, and frequency response from one quick and easy listening position to ensure clear and balanced surround-sound.



Accu**E**0 ROOM CALIBRATION

HDMI Video Up-Conversion

Only one wire! Every video signal is converted and sent to your TV through one HDMI cable.

Ready for Streaming Media Devices

The handy STRM Box port supplies power to streaming media players. Keep up with your video subscription services and other programs streamed from the Internet.

SPEC	וםוי	$\sim ^{1}$	Γ	NIC

A/V RECEIVER

Amp	lifier	Sect	ion
Power	Outpu	ıt	

Owei	Output		
All	Channels	11	15
		- 1	Cł

I I S W/Ch (6 Ohms, I kHz, 0.9% THD, I Channel Driven, FTC) 65 W/Ch (8 Ohms, 20 Hz–20 kHz, 0.7% THD, 2 Channels Driven, FTC)

160 W (3 Ohms, Front) 125 W (4 Ohms, Front) Dynamic Power 85 W (8 Ohms, Front) THD+N (Total Harmonic Distortion + Noise)

0.08% (20 Hz–20 kHz, Half Power)

Input Sensitivity and Impedance 200 mV/47 k-ohms (Line)

Rated RCA Output Level and Impedance I Vrms/470 Ohms (Subwoofer Pre Out)

Maximum RCA Output Level and Impedance 2V/470 Ohms (Subwoofer Pre Out) Frequency Response 10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode) ±10 dB, 20 Hz (Bass) ±10 dB, 20 kHz (Treble) Tone Control Signal-to-Noise Ratio 100 dB (Line, IHF-A) Speaker Impedance 6 Ohms–16 Ohms

Video Section

Input Sensitivity/Output Level and Impedance

1.0Vp-p/75 Ohms (Component Y) 0.7Vp-p/75 Ohms (Component PB/CB, PR/CR) 1.0Vp-p/75 Ohms (Composite) Video

Tuner Section Tuning Frequency Range 87.5 MHz-107.9 MHz 30 kHz-1,710 kHz FM/AM Preset Memory 40 Stations General

Power Consumption 4.3 A No-Sound Power Consumption

Standby Power Consumption

0.1 W Dimensions (W x H x D) 17 1/6" x 6 3/16" x 12 13/16" (435 x 160 x 328 mm) Weight 7.2 lbs. (7.8 kg)

SPEAKER SYSTEM

Front 2-Way, Bass Reflex
Height Full-Range, Acoustic-Suspension
Center 2-Way, Bass Reflex
Surround Full-Range, Acoustic-Suspension
Subwoofer Bass Reflex, Powered

Drivers Front

5" (12 cm) Cone Woofer 5 (12 cm) Cone Wooter
1" (2.5 cm) Balanced-Dome Tweeter
3 '/4" (8 cm) Cone
3 '/4" (8 cm) Cone Woofer x 2
1" (2.5 cm) Balanced-Dome Tweeter
3 '/4" (8 cm) Cone Surround Subwoofer 10" (25 cm) Cone

Frequency Response Front Height 55 Hz–50 kHz 80 Hz–20 kHz 65 Hz–50 kHz Surround 80 Hz-20 kHz 25 Hz-150 Hz

Output Sound Pressure Level

83 dB/W/m Height Center 81 dB/W/m 86 dB/W/m 81 dB/W/m

Max. Input Power Front/Height/Center/Surround

Rated Output Power

120 W (Minimum Continuous Power, 4 Ohms, 100 Hz, 1%, FTC) Front/Height/Center/Surround Nominal Impedance

Input Sensitivity/Impedance

Cubunofer 540 mV/20 k-ohms

Dimensions (W x H x D)
Front/Height

6 1/8" × 18 3/8" × 7 3/16" (155 × 467 × 183 mm) 6 1/8" × 4 1/2" × 4 3/4" (409 × 115 × 121 mm) 4 1/2" × 9 1/16" × 3 3/4" (115 × 230 × 96 mm) Center Surround 12 1/2" × 18 1/4" × 15 11/16" (317.5 × 463 × 398 mm) Subwoofer

Weight Front/Height 7.9 lbs. (3.6 kg) 4.9 lbs. (2.2 kg) 2.2 lbs. (1.0 kg) Center Surround 21.2 lbs. (9.6 kg)

CARTON	
Dimensions (W \times H \times D)	30 3/8" × 33 11/16" × 20 1/4"
	(772 × 855 × 514 mm)
Weight	77.2 lbs. (35 kg)
••••	······································

UPC CODE (B)

751398012273

Supplied Accessories

- Indoor FM antenna AM loop antenna Speaker setup microphone Color-coded speaker cables Subwoofer cable Instruction manual Remote controller AA (R6) batteries x 2

HT-R494









Text on receiver may vary with region.

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby, Atmos, Pro Logic, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited, DTS, DTS-HD, the Symbol, 8 DTS and the Symbol together are registered trademarks, and DTS-HD Master Audio is a trademark of DTS, Inc. @ DTS, Inc. All Rights Reserved HDMI, the HDMI logo, and high-Definition Multimeda Interface are trademarks or emplayed markers of HDMI logo, and the United States and other countries. The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. WRAT, Music Optimizer, CinemaFILTER. Theater Dimensional, and AccuEQ are trademarks of Onlyo Corporation. All other trademarks are the property of their respective holders.

